

Estándares de fabricación

| TECNOLOGIA | 12 MILS | 10 MILS | 8 MILS | 6 MILS |
|----------------------------------|--------------|--------------|--------------|--------------|
| DIAMETRO DE AGUJERO | 28 (0.70 mm) | 20 (0.50 mm) | 16 (0.40 mm) | 16 (0.40 mm) |
| DIAMETRO DE PAD O VIA | 50 (1.27 mm) | 40 (1.00 mm) | 32 (0.80mm) | 28 (0.70mm) |
| ANCHO DE TRAZA | 12 (0.30mm) | 10 (0.25 mm) | 8 (0.20 mm) | 6 (0.15mm) |
| SEPARACION ENTRE TRAZAS | 12 (0.30mm) | 10 (0.25 mm) | 7 (0.18 mm) | 6 (0.15mm) |
| SEPARACION ENTRE TRAZA Y PAD/VIA | 10 (0.25 mm) | 8 (0.20 mm) | 6 (0.15mm) | 6 (0.15mm) |
| DISTANCIA DE COBRE A BORDE | 12 (0.30mm) | 12 (0.30mm) | 12 (0.30mm) | 12 (0.30mm) |
| ALTURA - TRAZO DE LETRAS | 48 - 8 | 36 - 6 | 30-5 | 30-5 |



PRODUCCION 100% NACIONAL 



GESTION DE LA CALIDAD

RI-9000-3685

Acreditado por OAA



ISO 9001:2008

Carlos Pellegrini 1257/61
 (B1604ASG) Florida O. Bs. As - Argentina
 Tel. 5411) 4760-1322 rot. . Fax: (5411) 4761-1116
 mayer@pcb.com.ar - www.mayerpcb.com.ar

 **ERNESTO MAYER S.A.**
 CIRCUITOS IMPRESOS